


**SCB30UP6PC1**

Sensing Distance		Touch
Sensing Face		PC
Connection Type		1m Cable
Operational Voltage		12-30 VDC
Product		Capacitive Button
Type		Momentary
Feature		PLC Control 6 Wired
Mounting		Non Flush
Dia		30mm
Insulation Voltage	<b>Ui</b>	1500 VAC
Impulse Withstand Voltage	<b>Uimp</b>	75 VDC
Operating Temperature		-25°C...+70°C
Pollution Degree		3
Protection Degree		IP67
Number of Contact		1
Repeat Accuracy		<0,1 Sr
Output/Contact Type		PNP-NO
Reverse Polarity Protection		Available
Short Circuit Protection		Available
Max. Load Current		200 mA hiccup
Temperature Drift		<0,1 Sr
Time Delay Before Availability		≤100 ms
No Load Current		< 15 mA
Leakage Current		≤0,5mA
Min. Load Current		< 1mA
Voltage Drop		< 2 V
Ripple (Voltage)		< %10
EMC		61000-4-3 3V/m -- 61000-4-6 3

<b>Conditional Short Circuit Current</b>	100A
<b>Usage Category - Operating Current</b>	DC13 - 200mA
<b>Body Material</b>	Plastic
<b>Number of Cable and Cable Section</b>	6 x 0,25 mm <sup>2</sup>
<b>Serial</b>	SCB Series
<b>Specifications</b>	Rapid switching
	Easy to install to 30mm hole
	Short circuit and overload protection
	Reverse polarity protection
  	